Exterior Wood Cleaner

Efficient cleaner for exterior wood



Exterior Wood Cleaner is a preparatory cleaner for all types of exterior wood (decks, siding, fences, exterior doors, furniture, pergolas, etc.) and suitable composite surfaces. The product removes mill glaze, grey discolouration, green deposits, and dirt.

PRODUCT INFORMATION

› Specific characteristics

Benefits

- New wood:
  - Oily substances that appear naturally in some wood species are removed.
  - The wood pores are opened, which insures the finish will penetrate well and last longer.
  - Mill glaze on smooth, planed wood is removed.

- Wood previously treated with another brand's product:
  - **Surfaces previously treated with a penetrating finish:** If the finish has been exposed to full southern or western sun for more than one year, use Exterior Wood Cleaner to remove residues from previous applications. If the finish was applied less than one year ago and/or has not been exposed to weather, proceed to the next step.
  - **Surfaces previously treated with a paint, stain, or polyurethane/varnish:** Previous applications must be completely removed by sanding, stripping, or media blasting to expose bare wood before applying the finish.

Attention: Media blasting creates a rougher surface, which reduces the product's spread rate and results in a more intense final color. To minimize these effects, we recommend sanding the wood after media blasting before applying the finish.

› Technical characteristics

- Physical state: liquid
- Colour: transparent
- Odour: characteristic
- pH: 1.3
- Density: 0.99 kg/L

› Packaging



Bottle 100 ml



Jerrycan 1L



Jerrycan 5L

› Storage

The product can be stored for up to 24 months. Store in dry conditions and in the original packaging. Do not allow to freeze. Do not store above 86°F (30°C).

APPLICATION INFORMATION

› Instructions

STEP 1. Wet the wooden surface with a fine mist from a garden hose.

STEP 2. Apply Exterior Wood Cleaner generously.

STEP 3. Scrub the treated area with a stiff bristled nylon scrubbing brush (wear gloves and eye protection). This will cause the product to foam. For stubborn stains, repeat the application as needed.

STEP 4. Do not allow the cleaning solution to dry on the surface. Rinse thoroughly with clean water until all foaming residue has been removed. Do not use a pressure washer, as improper use may damage the wood surface.

STEP 5. Allow the surface to dry completely.

STEP 6. Apply the Rubio Monocoat exterior finish of our choice.

› Tips & tricks

- Good preparation is crucial to ensure a long lasting protective finish. All new, weathered, and previously treated wood must always be properly cleaned with Exterior Wood Cleaner.
- Avoid the use of Exterior Wood Cleaner near fish ponds, as this product is harmful to aquatic life.
- Wear gloves and eye protection to prevent any product from getting in your eyes or on your skin. This product is not harmful, however may cause eye or skin irritation.
- Exterior Wood Cleaner can also be used as a stand-alone treatment to improve the appearance of weathered wood, such as outdoor furniture after the winter. Results are visible immediately after application. *This product is not a finish and does not provide protection against UV exposure, moisture, or weathering.*

› Spread rate

Up to 150 ft²/L (15 m²/L)

** These usages are merely an estimate. Results depend on wood type, the degree of weathering, and method of preparation.*

Check the packaging and the safety data sheet for more details.

For our complete assortment of products for the protection and colouring of interior and exterior wood, please visit
www.rubiomonocoatusa.com
www.rubiomonocoatcanada.com

LIABILITY: It is the user's responsibility to establish, through his own tests, whether the product is suitable for the chosen application. In no case can Muylle Facon NV be held liable for any consequential damage. The information above may be subject to changes, which will be published in the updated versions of the technical data sheet. We cannot be held liable for poor results due to causes that are not related to the quality of the product. This technical information has been drawn up based on the currently available information and knowledge. The most recent technical data sheets can be requested or are available on the website.

Date of TDS: 08/07/2026. Check the safety information before using the product.

Muylle Facon NV
Ambachtenstraat 58
8870 Izegem (BELGIE)

Tel. +32 (0) 51 30 80 54
Fax +32 (0) 51 30 99 78
info@muyllefacon.be

www.rubiomonocoat.com